

KUBOTA CORPORATION

EXECUTIVE ORDER U-R-025-0060 New Off-Road Compression-Ignition Engines

Pursuant to the authority vested in the Air Resources Board by Sections 43013, 43018, 43101, 43102, 43104 and 43105 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following compression-ignition engine and emission control system produced by the manufacturer are certified as described below for use in off-road equipment. Production engines shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	ENGINE FAMILY	DISPLACEMENT (liters)	FUEL TYPE	USEFUL LIFE (hours)						
2002	2KBXL01.5BCD	1.123, 1.498	Diesel							
SPECIAL	FEATURES & EMISSION	CONTROL SYSTEMS	TYPICAL EQUIPMENT APPLICATION							
	Indirect Diesel Inje	ection	Compressor, Other Industrial Equipment							

The engine models and codes are attached.

The following are the exhaust certification standards (STD) and certification levels (CERT) for hydrocarbon (HC), oxides of nitrogen (NOx), or non-methane hydrocarbon plus oxides of nitrogen (NMHC+NOx), carbon monoxide (CO), and particulate matter (PM) in grams per kilowatt-hour (g/kw-hr), and the opacity-of-smoke certification standards and certification levels in percent (%) during acceleration (Accel), lugging (Lug), and the peak value from either mode (Peak) for this engine family (Title 13, California Code of Regulations, (13 CCR) Section 2423):

RATED	EMISSION			E	XHAUST (g/kw-l		OPACITY (%)				
POWER CLASS	STANDARD CATEGORY		НС	NOx	NMHC+Nox	co	PM	ACCEL	LUG	PEAK	
19 <u><</u> KW < 37	Tier 1	STD	N/A	N/A	9.5	5.5	0.80	20	15	50	
		CERT			6.0	1.4	0.51	10	8	17	

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the information and materials to demonstrate certification compliance with 13 CCR Section 2424 (emission control labels), and 13 CCR Sections 2425 and 2426 (emission control system warranty).

Engines certified under this Executive Order must conform to all applicable California emission regulations.

This Executive Order is only granted to the engine family and model-year listed above. Engines in this family that are produced for any other model-year are not covered by this Executive Order.

Executed at El Monte, California on this

_ day of November 2001.

R. B. Summerfield, Chief

Mobile Source Operations Division

Engine Model Immary Form

Manufacturer: KUBOTA Corporation

Engine category: Nonroad CI

EPA Engine Family. 2KBXL01.5BCD

Mfr Family Name: N/A

Process Code: New Submission

Attachment

4-18-28-60

1	1	· ·			:.								·					 -	T				
8.Fuel Rate: 9.Emission Control (lbs/hr)@peak torque Device Per SAE J1930						- Ac-								urraman de la									
ssion C Per SAE	AND.	¥	É	Ø	≸	≸	≸	≸ :	\$	¥	*	≨	≸	≸	¥.						,	dia constanti di managara	
9.Emi Device	Tal	أسب						-						,				 The second second second					989
e: orque	Ħ																						
uel Rate 2)peak t	7.4	9.1	9.2	12.2	11.2	9.4	8.8	8.6	9.2	84	8.3	.55 3.55	8.3	8.7	9.5			1					
8.F (lbs/hr)						A CONTRACTOR OF THE CONTRACTOR																	
_													٠.										
7.Fuel Rate: mm/stroke@peak torque	25.9	24.8	25.0	24.8	23.8	24.7	24.7	24.1	21.7	23.5	24.7	25.2	24.8	24.2	25.1								
7.F mm/st				and the second s						***************************************												and the second second	
M.	20	00	2	2	2	00	8	8	8	8	00	8	8	8	00								
6.Torque @ RPM (SEA Gross)	54.5@1700	52.7@2200	54.1@2200	72.2@2200	69.4@2100	72.5@1700	72.5@1600	70.7@1600	64.0@1900	65.3@1600	69.0@1500	70.9@1500	69.8@1500	68.2@1600	72.2@1700								-
6.Torqu (SE/	54.	52.	54.	72.	.69	72.	72.	70.	64	65.	.69	70.	69	68.	72.						•		
H S			And a company of the control of the																				
5.Fuel Rate: (lbs/hr) @ peak HP (for diesels only)	11.5	11.3	10.7	15.1	13.9	13.9	11.0	11.4	11.6	10.8	10.7	10.4	10.2	11.9	12.4								
5.Fu (lbs/hr) (for die																							
· - ·																in the state of							
il Rate: @ pea set only	22.9	22.5	22.7	22.5	21.8	22.2	21.3	21.2	21.7	22.0	22.8	23.3	22.9	20.5	21.4		III que proceso de constitución de la constitución	 5					
4.Fuel Rate: mm/stroke @ peak HP (for diesel only)																			,		-		:
															0			 -					
3.BHP@RPM (SAE Gross)	26.4@3000	26 n@3000	25 1@2800	35 5@3000	33,5@2850	33.5@2800	27.6@2300	28.4@2400	28.4@2400	26.0@2200	26.0@2100	24.8@2000	24 4@2000	28.2@2600	31.0@2600	- Prince control				The second secon			
3.BHP (SAE	26.46	26.06	25.16	35 50	33.56	33.5(27.6	28.4(28.4(26.0(26.0(24.8(24 4(28.20	31.00	and the Maria							
<u> </u>																					-		
Mode	7. IT	I Ц	ו ני	5 г 1 п	П П	1 1-50 15-E)5-E)5-E	V1505-E)5-E)5-E	V1505-E	T,	V1505-F	V1505-E			 					
2.Engine Model	D1105-F	D1105.F	1108 E	V1505-F	V1505-E	V1505-E	V1505-E	V1505-E	V15C	V1505-E	V1505-E	V150	V1505-F	745(V15(prominent transfer of the second					1	200	
			***************************************															 				5-8-8-8	
Code	Ţ	ם ו	7] <u>i</u>	Г Г	1 5	-E4	П.	9 - - -	E7	E8	-E	1 2	7 L	-E12								
1 Fnaine Code	04405 E4	0440F F2	77-00110	U1103-E3	V 1303-L 1 V/4505_E?	V1505-E2	V1505-E4	V1505-E5	V1505-E6	V1505-E7	V1505-E8	V1505-E9	V 1505 E10	V 1300-L 10	V1505-E11			 					
	: -							:			1	.İ			-			 				<u> </u>	